

TECHNICAL DATA

KAPTON® POLYIMIDE FILM TAPE

Product Code: 1K7172
(Flame Retardant)



P. Leo & Co Ltd

Email : sales@bcwire.net



 UL File No. E126174

Description : #1K7172 make by 1 mil Kapton® polyimide film tape with acrylic based thermosetting pressure sensitive adhesive complies with UL510 flame retardant requirements.

Features/Benefits : This product features toughness, puncture resistance, conformability and Class 180°C performance for electrical application.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	COLOR	-	amber
	TOTAL THICKNESS	mm (mil)	0.063 ± 0.006 (2.5)
	BACKING THICKNESS	mm (mil)	0.025 (1)
	TENSILE STRENGTH	kg/25mm (lb/in)	13.6 (29)
	ELONGATION AT BREAK	%	50
	ADHESIVE TO STEEL	kg/25mm (oz/in)	0.7 (24)
	BREAKDOWN VOLTAGE	kV	6.0
	TEMPERATURE CLASS	°C	180

Availability : Standard 33M roll, 3" core, width 630mm

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.



**HALOGEN
FREE**

