

TECHNICAL DATA

POLYESTER FILM TAPE

Product Code: 1P700



P. Leo & Co Ltd

Email : sales@bcwire.net



- Description : 1 mil polyester film with a thermosetting rubber adhesive system.
- Application : Coil banding, coil wrap - conformable to many irregular surfaces.
- Features/Benefits : Tough, thin abrasion resistant tape used in electrical applications requiring temperature performance to 130°C and a non-corrosive adhesive system.

Technical Details :	<u>PROPERTIES</u>	<u>UNIT</u>	<u>SPECIFICATION</u>
	COLOR	-	yellow
	TOTAL THICKNESS	mm	0.0625
	BACKING THICKNESS	mm	0.025
	TENSILE STRENGTH	kg/25mm	10.455
	ELONGATION AT BREAK	%	100
	ADHESION TO STEEL	kg/25mm	0.852
	BREAKDOWN VOLTAGE	kV	5
	TEMPERATURE CLASS	°C	130

Availability : Standard 66M roll, 3" core, width 600mm

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

