

TECHNICAL DATA

POLYESTER FILM TAPE

**Product Code: 1P9FR
(Flame Retardant)**



P. Leo & Co Ltd

Email : sales@bcwire.net



 UL File No. E126174

Description : 1P9FR is a 1-mil thick polyester film coated with a pressure sensitive Acrylic adhesive high dielectric strength, comfortable, tough and thin. This product complies with the flame Retardancy requirements of UL 510.

Application : Excellent for use in electric application, such as outer wrapping on capacitors and coils, holding transformer construction, harness wrap and so on. It is used as insulation material of class B.

Technical Details :	PROPERTIES	UNIT	SPECIFICATION
	COLOR	-	*see below
	TOTAL THICKNESS	mm	0.055 ± 0.005
	TENSILE STRENGTH	kg/25mm	9
	ELONGATION	%	70
	ADHESION TO STEEL	kg/25mm	0.6
	DIELECTRIC BREAKDOWN	kV	4
	TEMPERATURE CLASS	°C	130
	CORROSIVE FACTOR	-	0.98

*Color : RD = red YE = yellow BL = blue
GR = green BK = black WH = white

Test Method : In accordance with ASTM method

Shelf Life : 6 months when storage at 23°C and 65% relative humidity

Availability : Standard 66M roll, 3" core, width 980mm

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or *he inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection there with.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.

